

STRETCH-HOOD FILM

PRODUCT SHEET

Achieve all benefits of efficient and energy-saving packaging of your pallets with our premium stretch-hood film.

Our stretch hood film provides excellent protection of your pallets in external conditions, outstanding strength, elasticity, and excellent optical properties. Your palletized goods will be extremely tightly packed, using less material and with lower energy consumption. Our stretch-hood film is UV stabilized up to 24 months, is non-toxic and 100% recyclable.

ENVI

Under the ENVI label, we produce sustainable packaging material with a recycled raw material component (PCR) with a minimum content of 25%. Achieve higher level of environmental sustainability of your business with us – without compromising on the quality of your product packaging.

OPTI

Under the OPTI label, we offer you optimized film with a thickness reduced by up to 20%. Reduce your costs and maximize your value for money with our products. An additional benefit for you is a lower carbon footprint of your production.

DO YOU HAVE A QUESTION? CONTACT US! WE ARE HERE FOR YOU.



Mgr. Jozef Budovský

Sales Manager

+421 915 254 163

jozef.budovsky@petrio.sk



Mgr. Jurij Kazmiruk

Sales Manager

+421 911 629 672

kazmiruk@petrio.sk



FEATURES

- ✓ robust and reliable protection of packaged goods
- ✓ high transparency – good visual product communication
- ✓ lower film thickness without compromise on mechanical properties
- ✓ reliable UV stabilisation for extended lifespan
- ✓ wide range of film modification – including the use of recycled raw material components (PCR)
- ✓ 100% recyclability and health safety

APPLICATION

- > insulating materials
- > bricks, roof tiles
- > blocks
- > tiles
- > bags of loose material
- > white and black technology
- > glass and paper products

PRODUCT TYPE

- > stretch-hood film

DESIGN

- > tube
- > possibility of production with or without tabs

DIMENSIONS

width:	800 – 5200 mm (with tabs)
thickness:	65 – 200 µm
roll weight:	maximum 1000 kg
outside roll diameter:	up to 1200 mm
inner core diameter:	76 mm and 152 mm

MODIFICATIONS

- > transparent
- > coloured – varying degrees of opacity
- > UV stabilised (6 – 24 months)
- > antistatic – with protection against electrostatic charge
- > slip-resistant or non-slip
- > ionised
- > printed (maximum 6 colours)