

# SHRINK FILM

## PRODUCT SHEET

Secure your group-packed products with our high-strength sustainable shrink LDPE film. Your products will be safely protected during transport and storage.

Superior strength: Our shrink film is made from high-quality materials that are strong and durable. Excellent transparency of our sustainable LDPE film increases the visual appeal of the packaging content. Quality flexographic printing: enabling you to effectively communicate your brand messaging.

### ENVI

Sustainable packaging material from LDPE/HDPE with a recycled raw material component (PCR) with a minimum content of 25%. Achieve greater environmental sustainability for your business with us – without compromising on the quality of your product packaging.

### OPTI

Optimized film with up to 20% less material thickness. Reduce your material costs with us and achieve lower carbon footprint of your production.

DO YOU HAVE A QUESTION? CONTACT US! WE ARE HERE FOR YOU.



**Mgr. Jozef Budovský**

Sales Manager

+421 915 254 163

jozef.budovsky@petrio.sk



**Mgr. Jurij Kazmiruk**

Sales Manager

+421 911 629 672

kazmiruk@petrio.sk



**PETRIO, a.s.**

Vínárska cesta 1113

951 41 Lužianky, Slovakia

Business ID: 35823437

TAX ID: 2020225130

VAT no.: SK2020225130

BIC (SWIFT): OBKLSKBAXXX

IBAN: SK10 8370 0000 0061 6110 9282

www.petrio.sk



## FEATURES

- ✓ robust and reliable protection of packaged goods
- ✓ high transparency – effective visual product communication
- ✓ lower film thickness without compromise on mechanical properties
- ✓ wide range of film modification – including the use of recycled raw material components (PCR)
- ✓ 100% recyclability and health safety

## APPLICATION

- › various group-packaged products

## PRODUCT TYPE

- › shrink film

## DESIGN

- › flat film – HFFS (horizontal form-fill-seal) packaging lines
- › tube – tubular form-fill-seal (TFFS) packaging lines
- › half-tube

## DIMENSIONS

width:	50 – 2100 mm (tube circum. 6 m)
thickness:	20 – 200 µm
roll weight:	maximum 1000 kg
outside diameter of roll:	up to 1200 mm
inner core diameter:	76 mm and 152 mm

## MODIFICATIONS

- › transparent
- › coloured – varying degrees of opacity
- › UV stabilised (6 – 24 months)
- › antistatic – with protection against electrostatic charge
- › slip-resistant or non-slip
- › perforated
- › ionised
- › printed (maximum 6 colours)