

AGRICULTURE FILM

PRODUCT SHEET

Achieve enhanced yields from your land by utilizing our efficient mulching films and greenhouse films.

Streamline your production operations, especially in less favourable climatic conditions. Our PE mulch film will enable you to increase the efficiency of your production activities. Our PE film is enhanced with UV stabilisation for up to 24 months upon request, ensuring extended lifespan and safeguarding the root system under heightened temperatures. If required, our LDPE films are fully biodegradable and suitable for organic farming.

ENVI

Sustainable packaging material from LDPE/HDPE with a recycled raw material component (PCR) with a minimum content of 25%. Achieve greater environmental sustainability for your business with us – without compromising on the quality of your product packaging.

OPTI

Optimized film with up to 20% less material thickness. Reduce your material costs with us and achieve lower carbon footprint of your production.

DO YOU HAVE A QUESTION? CONTACT US! WE ARE HERE FOR YOU.



Mgr. Jozef Budovský

Sales Manager

+421 915 254 163

jozef.budovsky@petrio.sk



Mgr. Jurij Kazmiruk

Sales Manager

+421 911 629 672

kazmiruk@petrio.sk



FEATURES

- ✓ robust and reliable protection of agricultural production
- ✓ lower film thickness without compromise on mechanical properties
- ✓ reliable UV stabilisation for extended technical life
- ✓ wide range of film modification - including the use of recycled raw material components (PCR)
- ✓ 100% recyclability and health safety
- ✓ fully biodegradable production option

APPLICATION

- › agricultural primary production

PRODUCT TYPE

- › mulch film
- › foil for the construction of foil beds

DESIGN

- › flat film
- › tube
- › half-tube
- › possibility of production with or without gussets

DIMENSIONS

width:	400 - 2100 mm (tube circum. 6 m)
thickness:	20 - 200 µm
roll weight:	maximum 1000 kg
outside diameter of roll:	up to 1200 mm
inner core diameter:	76 mm and 152 mm

MODIFICATIONS

- › coloured - varying degrees of opacity
- › UV stabilised (6 - 24 months)
- › antistatic - with protection against electrostatic charge
- › slip-resistant or non-slip
- › perforated
- › ionised
- › printed (maximum 6 colours)